




Carbon Steel Hand Taps

BSF

Whitworth fine threads



HOLE TYPE



CS

BS
949

ZONE
5



Nominal Diameter	TPI	Overall Length	Thread Length	Shank Diameter	Square Size	Square Length	Tapping Drill Diameter	EDP No.
ØD1		L	L1	ØD3	a	L3	Ø d1	
3/16"	32	63.15	26.6	4.8	3.69	6.05	4	FBA0200842
7/32"	28	63.61	26.6	5.61	4.3	6.05	4.6	FBA0200870
1/4"	26	67.27	30.7	6.43	4.91	6.84	5.3	FBA0200898
9/32"	26	67.79	30.7	7.21	5.5	7.64	6.1	FBA0200926
5/16"	22	69.85	30.5	8	6.06	8.43	6.8	FBA0200954
3/8"	20	74.61	33.7	9.58	7.38	10.02	8.3	FBA0200982
7/16"	18	80.17	36.5	8.2	6.06	10.02	9.7	FBA0201011
1/2"	16	85.83	42.1	9.32	6.9	10.81	11.1	FBA0201039
9/16"	16	91.28	42	10.91	8.07	12.4	12.7	FBA0201067
5/8"	14	96.84	46	12.2	9.04	13.99	14	FBA0201095
11/16"	14	102.4	46	13.78	10.19	15.58	15.5	FBA0201123
3/4"	12	107.95	50.8	15	11.12	17.16	16.75	FBA0201151
7/8"	11	119.06	56.4	17.71	13.18	18.75	19.75	FBA0201207
1"	10	130.18	63.5	20.33	15.13	20.34	22.75	FBA0201263
1.1/8"	9	137.8	65	22.79	16.96	21.7	25.5	FBA0201291
1.1/4"	9	145.8	65	25.96	19.34	25.2	28.5	FBA0201319
1.3/8"	8	153.8	76	28.17	20.99	26.7	31.5	FBA0201347
1.1/2"	8	161.8	76	31.35	23.38	28.2	34.5	FBA0201375

CS TAPS